

**IEEE 100**  
**The Authoritative Dictionary of**  
**IEEE Standards Terms**

**Seventh Edition**

BE



Published by  
Standards Information Network  
IEEE Press

**BEST AVAILABLE COPY**

## Trademarks and disclaimers

*IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.*

*Other tradenames and trademarks in this document are those of their respective owners.*

*The Institute of Electrical and Electronics Engineering, Inc.  
3 Park Avenue, New York, NY, 10016-5997, USA*

*Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

*To order IEEE Press publications, call 1-800-678-IEEE.*

*Print: ISBN 0-7381-2601-2*

*SP1122*

*See other standards and standards-related product listings at: <http://standards.ieee.org/>*

*The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.*

*This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.*

## Contents

### Introduction

### How to Use

### Categories

### Trademarks

### The Author

### Abstracts and

### Non-IEEE Standards

## Library of Congress Cataloging-in-Publication Data

IEEE 100 : the authoritative dictionary of IEEE standards terms.—7th ed.  
p. cm.

ISBN 0-7381-2601-2 (paperback : alk. paper)

1. Electric engineering—Dictionaries. 2. Electronics—Dictionaries. 3. Computer engineering—Dictionaries. 4. Electric engineering—Acronyms. 5. Electronics—Acronyms. 6. Computer engineering—Acronyms. I. Institute of Electrical and Electronics Engineers.

TK9 .J28 2000  
621.3'03—dc21

00-050601

*The Authoritative*

**BEST AVAILABLE COPY**

layer.  
n of the physical layer appli-  
environment.

(C/MM) 1394-1995  
r to active CATV equipment  
the coaxial cable. This ac or  
th the RF information signal.

(LM/C) 802.7-1989r  
e or more cables out of a con-  
pose of repulling the cables.  
able pullback is normally per-  
a portion of a conduit system  
installation of additional cables.

(PE/IC) 1185-1994  
(s) into a conduit that already  
(PE/IC) 1185-1994  
red to the wall of a manhole,  
rovide support for cables.

(T&D/PE) [10]  
uctor cable is wound, includ-  
s and associated brushes, by  
cuit is made between the sta-  
ive or other mining device and  
on the drum. *Note:* The drum  
motor, a hydraulic motor, or  
the machine. *See also:* mine

(PE/EEC/MIN) [119]  
dition and control) A FAST-  
ible together with appropriate  
ices. (NID) 960-1993  
tion, underground cables) A  
s to separate two elements of  
ntamination or adhesion.

(PE) [4]  
vious metallic protective cov-  
able core.

(PE/T&D/IC) [4], [10]  
of cables) The outer covering  
provide mechanical and elec-  
tors. In telephone-type cables,  
ield, and may include armor.

(PE/PSC) 789-1988w  
ering applied to cables. *Note:*  
multiple layers, of which one  
(T&D) C2-1997, C2.2-1960

An insulator used to insulate  
sheath or armor from the me-  
transformer removable cable  
the supporting structure for  
le sheath currents. *See also:*  
able cable-terminating box.

(PE/TR) [107], [108]  
d control cables) A conduct-  
tal strands, ribbon or sheet  
p of wires, or cable, so con-  
p point on the surface of the  
rap is at ground potential or  
l with respect to ground. *See*

(PE/PSC) 789-1988w  
generating station) (cable  
ations) (shielding and shield  
allic material applied over the  
nductors to confine the elec-  
sulation of the conductor or  
EDPO) 422-1977, 690-1984r

ng or a specially formed band  
solder in joining ends of por-  
m. *See also:* mine feeder cir-  
(PE/EEC/MIN) [119]

(stems) The cable spreading  
nt to the control room where  
dispersed into various cable

## cable-system enclosure

trays for routing to all parts of the plant.

(PE/EDPG) 422-1977  
cable-system enclosure (nuclear power generating station)  
(cable-penetration fire stops, fire breaks, and system en-  
losures) An assembly installed around a cable system to  
maintain circuit integrity, for a specified time, of all circuits  
within the enclosure when it is exposed to the most severe  
fire that may be expected to occur in the area.

(PE/SUB/EDPG) 690-1984r, 525-1992r  
cable terminal (1) A device that provides insulated egress for  
the conductors. *Synonyms:* termination. (NESC) C2-1997  
(2) (power work) A device that seals the end of a cable and  
provides insulated egress for the conductors. *Synonyms:* pot-  
head; end bell. (PE/T&D) [10]

cable termination Parts assembled onto the end of the cable to  
provide the electrical and mechanical interface into the gas-  
insulated environment. Typically this includes a solid insu-  
lation barrier between the cable/cable fluid and the gas insu-  
lation of the GIS. (PE/IC) 1300-1996

cable tilt (loss) The amount of RF signal attenuation by a given  
coaxial cable. Cable attenuation is mainly a function of signal  
frequency, cable length, and diameter. Cables attenuate  
higher frequency signals more than lower frequency signals  
(tilt). Cable losses are usually referenced to the highest fre-  
quency carried (greatest loss) on the cable.

(LM/C) 802.7-1989r  
cable tray (1) (raceway systems for Class 1E circuits for nu-  
clear power generating stations) A prefabricated metal race-  
way with or without covers consisting of siderails and bottom  
support sections. Bottom support sections may be ladder,  
trough, or solid. (PE/NP) 628-1987r

(2) (electric power systems in commercial buildings) A unit  
or assembly of units or sections, and associated fittings, made  
of metal or other noncombustible material forming a contin-  
uous rigid structure used to support cables.

(IA/PSE) 241-1990r  
(3) A raceway resembling a ladder and usually constructed of  
metal. Other styles of trays include solid-bottom and channel  
type. (PE/IC) 848-1996

(4) A continuous rigid structure used to support cables. Cable  
trays include ladders, troughs, channels and other similar  
structures. Conduits are not included in this category.

(PE/IC) 817-1993w  
cable tray system (raceway systems for Class 1E circuits for nu-  
clear power generating stations) An assembly of metallic  
cable tray sections, fittings, supports, anchorages, and acces-  
sories that form a structural system to support wire and cables.

(PE/NP) 628-1987r  
cable trolley *See:* cable car.

cable TV A communication system that simultaneously distrib-  
utes several different channels of broadcast programs and  
other information to customers via a coaxial cable. Previously  
called community antenna television (CATV).

(LM/C) 802.7-1989r  
cable type (nuclear power generating station) A cable type  
for purposes of qualification testing shall be representative of  
those cables having the same materials, similar construction,  
and service rating, as manufactured by a given manufacturer.

(PE/NP) 380-1975w  
cable value *See:* manhole.

cab signal (1) A signal located in the engineman's compartment  
or cab indicating a condition affecting the movement of a train  
or engine and used in conjunction with interlocking signals  
and in conjunction with or in lieu of block signals. *See also:*  
automatic train control. (EEC/PE) [119]

(2) (system) A signal located in the cab, indicating a condi-  
tion affecting the movement of a train and used in conjunction  
with interlocking signals and in conjunction with or in lieu of  
block signals. (VT) 1475-1999

cache (1) A buffer inserted between one or more processors and  
the bus, used to hold currently active copies of blocks from  
main memory. (C/BA) 896.3-1993w

(2) A small portion of high-speed memory used for temporary  
storage of frequently-used data, instructions, or operands. *See*  
*also:* instruction cache; disk cache; high-speed buffer; cach-  
ing; cache architecture; data cache; cache memory.

(C) 610.10-1994w  
(3) *See also:* copy. (C/PA) 1328.2-1993w, 1224.2-1993w

cache coherence A system of caches is said to be coherent with  
respect to a cache line if each cache and main memory in the  
coherence domain observes all modifications of that same  
cache line. A modification is said to be observed by a cache  
when any subsequent read would return the newly written  
value.

(C/BA) 1014.1-1994w, 10857-1994, 896.3-1993w,  
896.4-1993w

cache agent A module that uses split transactions to assume all  
the rights and responsibilities of some number of remote  
cache modules. (C/BA) 896.4-1993w

cache line (1) Often called simply a "line." The unit of data on  
which coherence checks are performed, and for which coher-  
ence tag information is maintained. In SCI, a line consists of  
64 data bytes. (MM/C) 1596-1992

(2) Often called simply a "line." The block of memory (some-  
times called a "sector") that is managed as a unit for coher-  
ence purposes; i.e., cache tags are maintained on a per-line  
basis. SCI directly supports only one line size, 64 bytes.

(C/MM) 1596.5-1993  
(3) Often simply called a "line," the block of memory (some-  
times called a sector) that is managed as a unit for coherence  
purposes; i.e., cache tags are maintained on a per-line basis.

Although the SCI line size influenced the RamLink packet  
sizes, coherence protocols are beyond the scope of this stan-  
dard. (C/MM) 1596.4-1996

cache architecture (A) A computer architecture that employs  
an extremely high-speed memory block, called a cache, in  
which data is stored. (B) The organization of cache memory;  
for example, direct mapped cache, two-way set associative  
cache. (C) 610.10-1994

cache hit *See:* hit.

caching The process of accessing a cache. (C) 610.10-1994w

cache memory (1) A buffer memory inserted between one or  
more processors and the bus, which is used to hold currently  
active copies of blocks of information from main memory.

(C/BA) 1014.1-1994w  
(2) A buffer memory inserted between one or more proces-  
sors and the bus, used to hold currently active copies of blocks  
from main memory. Cache memories exploit spatial locality  
by what is brought into a cache. Temporal locality is exploited  
by the strategy employed for determining what is removed  
from the cache. (C/BA) 10857-1994, 896.4-1993w

CAD *See:* computer-aided design.

CADD *See:* computer-aided design and drafting.

CADEM *See:* computer-aided engineering; computer-aided  
manufacturing; computer-aided design.

CADF *See:* commutated antenna direction finder.

CADM *See:* computer-aided manufacturing; computer-aided  
design.

CAE *See:* computer-aided engineering; computer-aided  
education.

cage (1) A system of conductors forming an essentially contin-  
uous conducting mesh or network over the object protected  
and including any conductors necessary for interconnection  
to the object protected and an adequate ground. *See also:*  
Faraday cage. (EEC/PE) [119]

(2) emptydef. *See also:* aerial platform.  
(T&D/PE) 524-1992r

cage antenna A multi-wire element whose wires are so disposed  
as to resemble a cylinder, in general of circular cross section;  
for example, an elongated cage. (AP/ANT) 145-1993

**IEEE 100**  
**The Authoritative Dictionary of**  
**IEEE Standards Terms**

**Seventh Edition**



**IEEE**

Published by  
Standards Information Network  
IEEE Press

**BEST AVAILABLE COPY**

## Trademarks and disclaimers

*IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.*

*Other tradenames and trademarks in this document are those of their respective owners.*

*The Institute of Electrical and Electronics Engineering, Inc.  
3 Park Avenue, New York, NY, 10016-5997, USA*

*Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.*

*No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.*

*To order IEEE Press publications, call 1-800-678-IEEE.*

*Print: ISBN 0-7381-2601-2*

*SP1122*

*See other standards and standards-related product listings at: <http://standards.ieee.org/>*

*The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.*

*This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.*

## Library of Congress Cataloging-in-Publication Data

IEEE 100 : the authoritative dictionary of IEEE standards terms.—7th ed.  
p. cm.

ISBN 0-7381-2601-2 (paperback : alk. paper)

1. Electric engineering—Dictionaries. 2. Electronics—Dictionaries. 3. Computer engineering—Dictionaries. 4. Electric engineering—Acronyms. 5. Electronics—Acronyms. 6. Computer engineering—Acronyms. I. Institute of Electrical and Electronics Engineers.

TK9 .I28 2000  
621.3'03—dc21

00-050601

## Contents

### Introduction

### How to Use

### Categories

### Trademarks

### The Author

### Abstracts and

### Non-IEEE Standards

*The Authoritative*

**BEST AVAILABLE COPY**

yer.  
n of the physical layer appli-  
environment.

(C/MM) 1394-1995  
r to active CATV equipment  
the coaxial cable. This ac or  
th the RF information signal.

(LM/C) 802.7-1989r

e or more cables out of a con-  
urpose of repulling the cables  
able pullback is normally per-  
a portion of a conduit system  
installation of additional cables.

(PE/IC) 1185-1994

(s) into a conduit that already

(PE/IC) 1185-1994

ured to the wall of a manhole,  
rovide support for cables.

(T&D/PE) [10]

luctor cable is wound, includ-  
s and associated brushes, by  
is made between the statu-  
ive or other mining device and  
on the drum. *Note:* The drum  
motor, a hydraulic motor, or  
the machine. *See also:* mine

(PE/EEC/MIN) [119]

osition and control) A FAST-  
able together with appropriate  
ices.

(NID) 960-1993

tion, underground cables) A  
is to separate two elements of  
ntamination or adhesion.

(PE) [4]

vious metallic protective cov-  
able core.

(PE/T&D/IC) [4], [10]

of cables) The outer covering  
provide mechanical and elec-  
tors. In telephone-type cables,  
ield, and may include armor.

(PE/PSC) 789-1988w

ering applied to cables. *Note:*

multiple layers, of which one  
multiple layers, of which one

(T&D) C2-1997, C2.2-1960

An insulator used to insulate  
sheath or armor from the me-  
transformer removable cable

the supporting structure for  
le sheath currents. *See also:*

able cable-terminating box.

(PE/TR) [107], [108]

d control cables) A conduct-  
etal strands, ribbon or sheet

up of wires, or cable, so con-  
point on the surface of the

rap is at ground potential or

l with respect to ground. *See*

(PE/PSC) 789-1988w

generating station) (cable

ations) (shielding and shield

allic material applied over the

nductors to confine the elec-

ulation of the conductor or

EDPG) 422-1977, 690-1984r

ng or a specially formed band

solder in joining ends of por-

um. *See also:* mine feeder cir-

(PE/EEC/MIN) [119]

stems) The cable spreading

nt to the control room where

dispersed into various cable

trays for routing to all parts of the plant.

(PE/EDPG) 422-1977

**cable-system enclosure (nuclear power generating station)**  
(cable-penetration fire stops, fire breaks, and system en-  
losures) An assembly installed around a cable system to  
maintain circuit integrity, for a specified time, of all circuits  
within the enclosure when it is exposed to the most severe  
fire that may be expected to occur in the area.

(PE/SUB/EDPG) 690-1984r, 525-1992r

**cable terminal** (1) A device that provides insulated egress for  
the conductors. *Synonyms:* termination. (NESC) C2-1997

(2) (power work) A device that seals the end of a cable and  
provides insulated egress for the conductors. *Synonyms:* pot-  
head; end bell. (PE/T&D) [10]

**cable termination** Parts assembled onto the end of the cable to  
provide the electrical and mechanical interface into the gas-  
insulated environment. Typically this includes a solid insu-  
lation barrier between the cable/cable fluid and the gas insu-  
lation of the GIS. (PE/IC) 1300-1996

**cable tilt (loss)** The amount of RF signal attenuation by a given  
coaxial cable. Cable attenuation is mainly a function of signal  
frequency, cable length, and diameter. Cables attenuate  
higher frequency signals more than lower frequency signals  
(tilt). Cable losses are usually referenced to the highest fre-  
quency carried (greatest loss) on the cable.

(LM/C) 802.7-1989r

**cable tray** (1) (raceway systems for Class 1E circuits for nu-  
clear power generating stations) A prefabricated metal race-  
way with or without covers consisting of siderails and bottom  
support sections. Bottom support sections may be ladder,  
trough, or solid. (PE/NP) 628-1987r

(2) (electric power systems in commercial buildings) A unit  
or assembly of units or sections, and associated fittings, made  
of metal or other noncombustible material forming a contin-  
uous rigid structure used to support cables.

(IA/PSE) 241-1990r

(3) A raceway resembling a ladder and usually constructed of  
metal. Other styles of trays include solid-bottom and channel  
type. (PE/IC) 848-1996

(4) A continuous rigid structure used to support cables. Cable  
trays include ladders, troughs, channels and other similar  
structures. Conduits are not included in this category.

(PE/IC) 817-1993w

**cable tray system (raceway systems for Class 1E circuits for**  
nuclear power generating stations) An assembly of metallic  
cable tray sections, fittings, supports, anchorages, and acces-  
sories that form a structural system to support wire and cables.

(PE/NP) 628-1987r

**cable trolley** *See:* cable car.

**cable TV** A communication system that simultaneously distrib-  
utes several different channels of broadcast programs and  
other information to customers via a coaxial cable. Previously  
called community antenna television (CATV).

(LM/C) 802.7-1989r

**cable type (nuclear power generating station)** A cable type  
for purposes of qualification testing shall be representative of  
those cables having the same materials, similar construction,  
and service rating, as manufactured by a given manufacturer.

(PE/NP) 380-1975w

**cable value** *See:* manhole.

**cab signal** (1) A signal located in the engineman's compartment  
or cab indicating a condition affecting the movement of a train  
or engine and used in conjunction with interlocking signals  
and in conjunction with or in lieu of block signals. *See also:*  
automatic train control. (EEC/PE) [119]

(2) (system) A signal located in the cab, indicating a condi-  
tion affecting the movement of a train and used in conjunction  
with interlocking signals and in conjunction with or in lieu of  
block signals. (VT) 1475-1999

**cache** (1) A buffer inserted between one or more processors and  
the bus, used to hold currently active copies of blocks from  
main memory. (C/BA) 896.3-1993w

(2) A small portion of high-speed memory used for temporary  
storage of frequently-used data, instructions, or operands. *See*  
*also:* instruction cache; disk cache; high-speed buffer; cach-  
ing; cache architecture; data cache; cache memory.

(C) 610.10-1994w

(3) *See also:* copy. (C/PA) 1328.2-1993w, 1224.2-1993w

**cache coherence** A system of caches is said to be coherent with  
respect to a cache line if each cache and main memory in the  
coherence domain observes all modifications of that same  
cache line. A modification is said to be observed by a cache  
when any subsequent read would return the newly written  
value.

(C/BA) 1014.1-1994w, 10857-1994, 896.3-1993w,  
896.4-1993w

**cache agent** A module that uses split transactions to assume all  
the rights and responsibilities of some number of remote  
cache modules. (C/BA) 896.4-1993w

**cache line** (1) Often called simply a "line." The unit of data on  
which coherence checks are performed, and for which coher-  
ence tag information is maintained. In SCI, a line consists of  
64 data bytes. (MM/C) 1596-1992

(2) Often called simply a "line." The block of memory (some-  
times called a "sector") that is managed as a unit for coher-  
ence purposes; i.e., cache tags are maintained on a per-line  
basis. SCI directly supports only one line size, 64 bytes.

(C/MM) 1596.5-1993

(3) Often simply called a "line," the block of memory (some-  
times called a sector) that is managed as a unit for coherence  
purposes; i.e., cache tags are maintained on a per-line basis.  
Although the SCI line size influenced the RamLink packet  
sizes, coherence protocols are beyond the scope of this stan-  
dard. (C/MM) 1596.4-1996

**cache architecture** (A) A computer architecture that employs  
an extremely high-speed memory block, called a cache, in  
which data is stored. (B) The organization of cache memory;  
for example, direct mapped cache, two-way set associative  
cache. (C) 610.10-1994

**cache hit** *See:* hit.

**caching** The process of accessing a cache.

(C) 610.10-1994w

**cache memory** (1) A buffer memory inserted between one or  
more processors and the bus, which is used to hold currently  
active copies of blocks of information from main memory.

(C/BA) 1014.1-1994w

(2) A buffer memory inserted between one or more proces-  
sors and the bus, used to hold currently active copies of blocks  
from main memory. Cache memories exploit spatial locality  
by what is brought into a cache. Temporal locality is exploited  
by the strategy employed for determining what is removed  
from the cache. (C/BA) 10857-1994, 896.4-1993w

**CAD** *See:* computer-aided design.

**CADD** *See:* computer-aided design and drafting.

**CADEM** *See:* computer-aided engineering; computer-aided  
manufacturing; computer-aided design.

**CADF** *See:* commutated antenna direction finder.

**CA DM** *See:* computer-aided manufacturing; computer-aided  
design.

**CAE** *See:* computer-aided engineering; computer-aided  
education.

**cage** (1) A system of conductors forming an essentially contin-  
uous conducting mesh or network over the object protected  
and including any conductors necessary for interconnection  
to the object protected and an adequate ground. *See also:*  
Faraday cage. (EEC/PE) [119]

(2) emptydef. *See also:* aerial platform.

(T&D/PE) 524-1992r

**cage antenna** A multi-wire element whose wires are so disposed  
as to resemble a cylinder, in general of circular cross section;  
for example, an elongated cage. (AP/ANT) 145-1993